



TECHNICAL SPECIFICATIONS

Product Catalog Number:
L250

Physician Display:
2560 x 1440 pixels

Lab Auxiliary Display Output:
1920x1080 pixels (HDMI)

Operator Touch Display:
1920 x 1080 pixels

Catheter Rotational Speed:
30, 45, 60 RPM - Ocelot Family
1000 RPM - Pantheris Family

Data Storage Capacity:
1500 hours video

OCT Technology:
Common Path


LIGHTBOX

A reusable, multi-display, mobile unit designed to deliver OCT images.
Lightbox is here to shed light on all our PAD procedures.

REAL TIME OCT

Receive continuous feedback to help guide crossing.

FLUORO SYNCHRONIZATION

Ability to correlate medial/lateral position on Lightbox with fluoroscopy.

MULTIPLE DEVICES

Plays nice with all Avinger OCT image guided catheters and accessories.

SPEED BOOST

Pantheris cutter rotates at 1000 RPM using Lightbox | SLED.

MEDIA CAPABILITIES

Image and movie capture, zoom, playback and export.

MOBILE

Anywhere in the lab. Use in multiple labs. Connect to lab monitor.

Lightbox is intended for use in peripheral vasculature procedures in conjunction with a compatible Avinger product.